Liquid Fertilizer Pumps



ShurFlow Automatic-Demand Pumps - 12 VDC

SHURflo 2088 Series diaphragm pumps deliver reliable performance in high flow, moderate pressure applications. They are used in a variety of spot spraying, multi-tip spraying and fertilizer drip applications that require flow of up to 3.6 GPM (13.6l/min). They are available in a variety of chemical-resistant materials.

KEY FEATURES:

- Chemical resistant materials
- Can run dry without damage
- Automatic demand
- Built in check valve (varies by model) prevents back flow of fluid into the solution tank
- Continuous duty motor on fin cooled version.

Agricultural use Diaphram Pumps

DESCRIPTION	*PART #*
12 volt Diaphram pump	HY2088514500
115v Diaphram pump	HY2088393120



DESCRIPTION	*PART #*
Replacement Head for pump	HY9491001

Shurflo 5 gpm Pump



FEATURES:

- Delivers 5 GPM free Flow - 4 GMP at 40 PSI with current draw of 13 amps
- Field-proven pump head design
- Driven by a 12 volt, continuous-duty, sealed motor
- Self-priming capabilities, up to 8 ft.
- Santoprene® diaphragm for chemical resistance
- Viton® valves provide maximum chemical resistance
- Built-in pressure switch, set at 60 PSI, protects the pump in the event of dead heading
- Available in the same footprint as other SHURflo pumps, allowing users to upgrade to a higher performance on existing installations

DESCRIPTION	*PART #*
5 GPM Continuos Flow Pump	HY50599131D011



DESCRIPTION	*PART #*
Replacement Head	HY9423800

Hypro 4000 sereies electric driven roller pump



STANDARD FEATURES:

The 4000 series, 4 roller pump achieves up to 10.4 gpm
3/4" NPT ports

- Super Rollers standard provide premium wear life available in Poly and PTFE for superior chemical resistance
- Viton® seals offer the best overall chemical resistance
- Pump direct coupled to a 12 volt DC motor
- Includes locking collar and torque arm

DESCRIPTION	*PART #*
12 volt electric powered 4 roller pump	HY4001XLEHT3