

# Storage Tanks

## Tanks



### Pattison FERTANK

#### STANDARD FEATURES:

- Large capacity - Holds a complete B-train load of liquid fertilizer...with room to spare
- Lower cost - Polyethylene FERTANK costs significantly less than steel or fiberglass tanks
- Corrosion proof - Fertilizer will not corrode the polyethylene material. Inner and/or outer coating (or maintenance re-coating) are not required
- Heavy duty - The FERTANK is designed to store fertilizer, with a thicker wall than standard poly tanks to accommodate fertilizer's greater weight
- Durable - Polyethylene is a very durable material with a long, maintenance free, life
- Easier to move - Polyethylene is lighter than steel so the tanks are easier to move and transport
- Molded in lugs - Provide a convenient attachment point for loading or moving lifting empty tanks and for holding down tanks during transport or on site
- Lid - Large 22" diameter lid
- Fittings - 3" threaded fitting standard. 1" through 4" fitting available
- Vent - Standard vent located on top of tank
- 1" of sidewall is approximately 65 gals.
- Comes with either 2" or 3" Banjo valve packages

DESCRIPTION	PART#
FERTANK 8250 Imp. gal. tank	QMP706831



### Liquistor Stainless Steel Storage Tanks

#### STANDARD FEATURES:

- Flat bottom dome style tank
- Made from 304 stainless steel
- 1 - 24" manway for easy tank access
- 2 - 4" FPT tank fittings for recirculation and fill/discharge
- 3/4" auto shutoff valve and sight gauge
- Lifting lugs
- Backed by a two year warranty
- Sight gauge tank volume measurements

#### Stainless Steel Tanks Offer:

- Superior corrosion resistance to regular steel tanks
- Competitively priced to other storage tanks
- Proven record, for trouble free storage of liquid fertilizers
- Maintenance free with little upkeep
- Manufactured in Canada by highly experienced company backed by a two year warranty

DESCRIPTION/ CAPACITY	Model
25,630 Imp. Gal.(30,750 US) / 148 t.	1620 - 16' Dia. x Height - 23'6"
31,890 Imp.Gal. (38,268 US) / 184 t.	1625 - 16' Dia. x Height - 28'6"
38,160 Imp.Gal. (45,800 US) / 220 t.	1630 - 16' Dia. x Height - 33'6"
44,420 Imp.Gal. (53,304 US) / 260 t.	1635 - 16' Dia. x Height - 38'6"
50,680 Imp.Gal. (60,800 US) / 293 t.	1640 - 16' Dia. x Height - 43'6"
56,300 Imp. Gal. (67,560 US) / 325 t.	1835 - 18' Dia. x Height - 38'6"
64,230 Imp. Gal. (77,076 US) / 370 t.	1840 - 18' Dia. x Height - 43'8"
79,664 imp. Gal. (95,570 US) / 470 t.	1850 - 18' Dia. x Height - 53.8"

### Replacement Manway Gaskets

DESCRIPTION	PART#
18" Manway Gasket	MER18820
24" Manway Gasket	MER18079