Couplings and Fittings

















Polypropylene Couplings

STANDARD FEATURES:

- Stainless steel rings, arms & pins
 Most complete line of polypropylene couplings available
 Versatile interchangeable with all types of cam lever couplers
 Precision molded insures a uniform and accurate fit

- Durable polypropylene is glass filled for rugged strength & durability
 Smooth operating finger rings are designed for easy opening of cam levers
- Complete series of 1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 3" and 4" NPT thread. BSP threads available 1" 3" sizes (excluding 1 1/4")
 Operating conditions: 3/8" thru 2" 100 P.S.I. at 0°F; 125 PSI at 70°F; 70 PSI at 150°F, 2 1/2", 3" & 4" Cap 50 PSI Couplings 75 PSI max.
 Economical and superior in performance
 Standard with EPDM gaskets. Buna "N" and FKM (viton type) also available

A Coupling

Е

DESCRIPTION	PART #
Coupler, male cam x female thread 3/4"	BA075A
Coupler, male cam x female thread 1"	BA100A
Coupler, male cam x female thread 1 1/4"	BA125A
Coupler, male cam x female thread 1 1/2"	BA150A
Coupler, male cam 1 1/2" x female thread 1 1/4"	BA150125A
Coupler, male cam x female thread 2"	BA200A
Coupler, male cam x female thread 3"	BA300A
Coupler, male cam x female thread 4"	BA400A

B Coupling

DESCRIPTION	PART #
Coupler, female cam x male thread 3/4"	BA075B
Coupler, female cam x male thread 1"	BA100B
Coupler, female cam x male thread 1 1/4"	BA125B
Coupler, female cam x male thread 1 1/2"	BA150B
Coupler, female cam 1 1/2" x male thread 1 1/4"	BA150125B
Coupler, female cam x male thread 2"	BA200B
Coupler, female cam x male thread 3"	BA300B
Coupler, female cam x male thread 4"	BA400B

C Coupling

DESCRIPTION	PART #
Coupler, female cam x hose shank 3/4"	BA075C
Coupler, female cam x hose shank 1"	BA100C
Coupler, female cam x hose shank 1 1/4"	BA125C
Coupler, female cam x hose shank 1 1/2"	BA150C
Coupler, female cam x hose shank 1 1/2" 90°	BA15090
Coupler, female cam 1 1/2" x hose shank 1 1/4"	BA150125C
Coupler, female cam x hose shank 2"	BA200C
Coupler, female cam x hose shank 2", 90°	BA200C90
Coupler, female cam x hose shank 3"	BA300C
Coupler, female cam x hose shank 4"	BA400C

D Coupling

DESCRIPTION	PART #
Coupler, female cam x female thread 3/4"	BA075D
Coupler, female cam x female thread 1"	BA100D
Coupler, female cam x female thread 1 1/4"	BA125D
Coupler, female cam x female thread 1 1/2"	BA150D
Coupler, female x female thread 1 1/2", 90°	BA150D90
Coupler, female cam 1 1/2" x female thread 1"	BA150125D
Coupler, female cam x female thread 2"	BA200D
Coupler, female x female thread 2", 90°	BA200D90
Coupler, female cam x female thread 3"	BA300D
Coupler, female cam x female thread 4"	BA400D



Couplings and Fittings



E Coupling

DESCRIPTION	PART #
Adapter, male cam x hose shank 3/4"	BA075E
Adapter, male cam x hose shank 1"	BA100E
Adapter, male cam x hose shank 1 1/4"	BA125E
Adapter, male cam x hose shank 1 1/2"	BA150E
Adapter, male cam 1 1/2" x hose shank 1 1/4"	BA150125E
Adapter, male cam x hose shank 2"	BA200E
Adapter, male cam x hose shank 3"	BA300E
Adapter, male cam x hose shank 4"	BA400E

F Coupling

DESCRIPTION	PART #
Adapter, male cam x male thread 3/4"	BA075F
Adapter, male cam x male thread 1"	BA100F
Adapter, male cam x male thread 1 1/4"	BA125F
Adapter, male cam x male thread 1 1/2"	BA150F
Adapter, male cam x male thread 1 1/2", 90°	BA150F90
Adapter, male cam 1 1/2 x male thread 1 1/4"	BA150125F
Adapter, male cam x male thread 2"	BA200F
Adapter, male cam x male thread 2", 90°	BA200F90
Adapter, male cam x male thread 3"	BA300F
Adapter, male cam x male thread 4"	BA400F

Coupling Cap

DESCRIPTION	PART #
Cap, camlock, 3/4" (Fits 1/2" & 3/4")	BA075CAP
Cap, camlock, 1" (Fits 1" & 1 1/4")	BA100125CAP
Cap, camlock, 1 1/2"	BA150CAP
Cap, camlock, 2"	BA200CAP
Cap, camlock, 3"	BA300CAP
Cap, camlock, 4"	BA400CAP

Coupling Plug

DESCRIPTION	PART #
Plug, male cam (Fits 1/2" & 3/4")	BA075PL
Plug, male cam (Fits 1" & 1 1/4")	BA100125PL
Plug, male cam, 1 1/2"	BA150PL
Plug, male cam, 2"	BA200PL
Plug, male cam, 3"	BA300PL
Plug, male cam, 4"	BA400PL









STANDARD FEATURES:

- Precision molded in polypropylene, reinforced with fiberglass for strength and durability
- Stainless steel rings, cam levers and pins resist corrosion
 Banjo 90° angle couplings and adapters will reduce the number of elbows and other pipe fittings used in plumbing applications
 • EPDM gasket, 125 max. psi

A 90° Coupling

DESCRIPTION	PART #
90° male adapter 1 1/2" female thread	BA150A90
90° male adapter 2" female thread	BA200A90

Coupling Replacement Gasket Parts

DESCRIPTION	PART #
Gasket, EPDM, 3/4"	BA075G
Gasket, EPDM extra thick, 3/4"	BA075GXT
Gasket, EPDM, 1"	BA100G
Gasket, EPDM 1" extra thick	BA1000GXT
Gasket, EDPM 1 1/2" extra think	BA150GXT
Gasket, EPDM, 1 1/2"	BA150G
Gasket, EPDM, 2"	BA200G
Gasket, EPDM extra thick, 2"	BA200GXT
Gasket, EPDM, 3"	BA300G

C 90° Coupling

DESCRIPTION	PART #
90° female coupler, 1 1/2" hose shank	BA150C90
90° female coupler, 2" hose shank	BA200C90

D 90° Coupling

DESCRIPTION	PART #
90° female coupler, 1 1/2" female thread	BA150D90
90° female coupler, 2" female thread	BA200D90
F 90° Counting	

DESCRIPTION	PART #
90° male adapter 1 1/2" male thread	BA150F90
90° male adapter 2" male thread	BA200F90





Couplings and Fittings







3" w/3 Arms Poly Cam Lever Couplings

DESCRIPTION	PART #
3" Female coupler/2" male adapter	BA303B200A

Poly Cam Lever Couplings		
DESCRIPTION	PART #	
3" Female coupler - 3" extended male thread	BA303B	
3" Female coupler 3 arms 3" hose shank	BA303C	







Spool Adapters		
DESCRIPTION	PART #	
2" Male adapter - 2" male adapter	BA200FF	
3" Male adapter - 2" male adapter	BA300F200F	
3" Male adapter - 3" male adapter	BASOOFF	



Flanged Check Valve

Flanged Check Valve	
PART #	
BAMCV200	
BAMCV220	
BAMCV300	
_	



1 pint Tru-Blu sealant

Pipe Sealant DESCRIPTION PART # 1 3/4 oz. Tru-Blu sealant PP31780 1/4 pint Tru-Blu sealant PP31631 PP31551 1/2 pint Tru-Blu sealant



PP31431