Storage Tanks



DESCRIPTION/ CAPACITY

30,750 US GAL.- 23'6"

38.268 US GAL.- 28'6"

45,800 US GAL. - 33'6"

53,304 US GAL. - 38'6"

60,800 US GAL. - 43'6"

58,068 US GAL. - 33'6"

67,560 US GAL. - 38'6"

77,050 US GAL. - 43'6"

95,550 US GAL. - 48'6"

Liquistor Stainless Steel Storage Tanks STANDARD FEATURES:

- · Flat bottom dome style tank
- · Made from 304 stainless steel
- 1 24" manway for easy tank access
- 2 4" FPT tank fittings for recirculation and fill/discharge
- 3/4" auto shutoff valve and sight gauge
- Lifting lugs
- Backed by a two year warranty
- · Sight gauge tank volume measurements

Stainless Steel Tanks Offer:


- · Superior corrosion resistance to regular steel tanks
- · Competitively priced to other storage tanks
- · Proven record, for trouble free storage of liquid fertilizers
- · Maintenance free with little upkeep
- · Manufactured in Canada by highly experienced company backed by a two year warranty

Replacement Manway Gaskets	
DESCRIPTION	PART#
18" Manway gasket – 20 Bolt	MER18820
24" Manway gasket – 20 Bolt	MER18079

AirMix Liquid Fluidizer

STANDARD FEATURE:

The new AirMix Liquid Fluidizer is a computerized system of pulsating air injection across the bottom of the tank to agitate and suspend liquids. Ensure your liquids are ready to go with the Meridian AirMix. Users can select the speeds and settings of the pulsing action with Meridian's Variable Control System, changing the duration and frequency of the air agitation within the tank. Gentle mixing action, low compressor HP requirements and full automation make the AirMix a great feature on any liquid storage tank.



Positioned on the base of the floor are four air discharge chambers to allow even pulsating distribution throughout



Control panel will allow operator to increase air flow and change speed of pulsating



Control panel installed with the air line feeding the four floor mounted pulsating discharge chambers

AirMix System	
DESCRIPTION	PART#
AirMix floor package	MER40623
AirMix Control panel	MER40622

Model

Model 1620 - 151t.

Model 1625 - 188t.

Model 1630 - 224t

Model 1635 - 261t.

Model 1640 - 298t.

Model 1830 - 262t.

Model 1835 - 331t.

Model 1840 - 378t.

Model 1850 - 433t.

