



Shown with Micro-matic adapter



Shown with optional meter and hose.

Operating Parameters:

- Flows to 38l/m (10 gpm) at 16°C (60°F)
- Pressures to 1.7 bar (25psi)
- Temperatures to 55°C (130°F)
- 115-volt AC operated motor with 6.1 m (20 ft) cable; 12-volt DC motor optional



DEF Nozzle

DESCRIPTION	PART #
Def Nozzle Assy	FSPH89

Diesel Exhaust Fluid (DEF) Pumps

DESCRIPTION	PART #
PH6 DEF Pump 12 volt (no micro-matic fitting)	old # FSPH6PDEF new # FSCT6DEF
PH6 DEF Pump 110 volt (no micro-matic fitting)	FSPH6110DEF
PH6 DEF pump 12 volt	old # FSPH6MMDEF new # FSCT6MMDEF
PH6 DEF pump 110 volt	FSPH6110DEFMM
Dip Tube	FSXTUBETE
Dip Tube fitting	FSPH25

STANDARD FEATURES:

- Vertical or horizontal container top mount
- Removable cartridge containing diaphragm, valves and bypass assembly eases maintenance and field replacement
- Multiple pump-chamber design or increased dependability
- EPDM seals standard
- 2-Year service program on standard duty DEF pumps and pump mounted flow meters
- Pump meter and hose shown as options

Note: dip-tubes and fittings are not included with DEF Pump only

Replacement Parts for PH6 Pumps



Pump housing body



PH6 Motor only



Oring & gasket kit

DESCRIPTION	PART #
Pump Housing	FSPH6KIT02
PH6 Motor Only	FSPH6M01
Cartridge and Gasket Kit	FSPHPKIT01V
Oring and Gasket Kit	FSPHPKIT02V
12' Discharge Hose	FSEP5804
1" Valve For Hose	BAUV100FP
Valve Nozzle	BAV10161
1" Valve c/w nozzle	FSPH20



Discharge hose, valve & nozzle



Cartridge & gasket kit



1" valve c/w nozzle